MAJESTIC ULTRA

Detergent powder compatible with ultra filtration systems

UMBRELLA DESCRIPTION

- Majestic powders are highly efficient detergent powders that can be used to process laundry for the hospitality, healthcare and workwear industry.
- ✓ Majestic products are developed to be combined with Peracetic acid products.
- ✓ Ideal wash temperatures for Majestic powders are between 65°C and 90°C.

PROPERTIES

FABRIC WASHING

- Robust performance on white and coloured fabrics, esp. work wear.
- Contains natural soap giving a better ironing performance.
- Good soil suspending capacity.
- Heavy duty laundry powder for white and coloured flat and work wear, cotton and polyester-cotton.
- Compatible with ultra filtration systems.
- Can be used for all wash and machine systems in soft to medium hard water.
- Suitable for automatic dosing or in stock solution applications.

USE INSTRUCTIONS

Recommended dosage g/kg dry fabrics:

- Light 5 10 g/kg
- Medium 10 15 g/kg
- Heavy 15 20 g/kg

COMPOSITION ACCORDING EC-DIRECTIVE

< 5 % phosphonates, non-ionic and anionic surfactants, soap

15 - 30 % phosphates

Contains also carbonates, silicates, stabilisers, dispersants and optical brightener.





PHYSICO-CHEMICAL PROPERTIES

- Density: •
- 0.86 g/ml (untapped)
- 0.93 g/ml (tapped)
- Total alkalinity (1%): 6.50 g/l (Na₂CO₃) •
- Active alkalinity (1%): 2.55 g/l (Na₂O) • 12.2
- pH (1%):

LEGISLATION

Surfactants in Majestic Ultra comply with the European Union Directive EU648/2004 on the biodegradability of surfactants.

Does not contain alkyl phenol ethoxylates, EDTA, NTA. COD-value: 170.057 mg/kg.

SAFETY AND TRANSPORT



GHS05 GHS07

UN 3253

Meets European directives on the classification, packaging and labelling of dangerous chemical substances and preparations.

STORAGE

Store in a cool and dry place.

PACKAGING

Bag 25 kg **Big Bag** 250 kg

NON WARRANTY

The suggestions and data in this bulletin are based on information we believe to be reliable. They are offered in good faith but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determines the suitability of our products on an experimental basis before adopting them in a real-life situation. Please contact our technical representatives for more information.



